

**Gunpowder / Euro Oak (FSC certified) / Rustic Plank**



Usage	Commercial & Residential Applications
Product Code	2WOR[THICKNESS]X180GP F
Thickness x Width	15 x 180, 20 x 180mm
Board Type	Engineered T&G
Pattern	1-strip plank (micro-bevel 2 sides)
Pack Length	1.8m, 2.1m, 2.4m (allowing 1 split board/pack)
Top Layer	4mm on 15mm thick & 6mm on 20mm thick
Timber Grade	Good rustic or character grade
Backing	Birch plywood
Surface Finish	Smoked, brushed, grey then clear oiled
Environmental Rating	A+
Maintenance	Follow <i>Maintenance for Hardwax Oiled Floors</i>

**Installation** All floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Please check your installer is approved to BS8201.

Installation Methods	
Fully Bonded	Yes * recommended
Nailed	Yes
Floated over Underlay	Yes
Over Underfloor Heating	Yes * **

\* Subject to compatible subfloor and correct installation (see installation guidelines).

\*\* Subfloor temperature must never be allowed to exceed 27 degrees centigrade.

**Gunpowder / Euro Oak (FSC certified) / Rustic Plank**



<b>Grading Criteria</b>	
Maximum Knot Size	No maximum
Filled Defects	Allowed
Heart / Pith	Not allowed
Sapwood	Not allowed
End Checks / Cracks	Filled & sanded <1mm wide & <100mm long
Insect Damage	Not allowed
Filler	Allowed
Colour Variation	Natural variation allowed

N.B. Grading criteria is an approximation. Please allow for variation.

Origin	EU
EUTR	EUTR compliant
FSC	Yes
PEFC	-
SVLK	-
Moisture Content	8 - 10%
Janka Hardness Rating (Euro Oak)	1,360 lbf
Slip Testing	65 PTV
Fire Classification	15mm Cfl-s1, 20mm Dfl-s1
Thermal Conductivity	15mm 0.11 W/m K, 20mm 0.17 W/m K
Emission of (release) formaldehyde	E1
Breaking Strength (max. load)	20/6 - 5.4kN (60cms) 6.2kN (40cms), 15/4 - N/A
Cigarette Burns	Not easily repairable
Stain Resistance	Good
Acoustic Properties	N/A