

**Unfinished / Euro Oak (FSC certified) / Rustic Blocks**

Page 1/2



Usage	Commercial & Residential Applications
Product Code	2WOBR15X70X230F, 2WOBR15X105X60F
Thickness x Width	15/4 x 70mm, 15/4 x 105mm
Board Type	Engineered (70mm No T&G)
Pattern	1-strip herringbone block flooring
Pack Length	230mm (70mm), 600mm (105mm)
Top Layer	4mm
Timber Grade	Rustic grade
Backing	Birch ply
Surface Finish	Unfinished
Environmental Rating	A+
Maintenance	Appropriate maintenance for finish applied

**Installation** All floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Please check your installer is approved to BS8201.

Installation Methods	
Fully Bonded	Yes *
Nailed	No
Floated Over Underlay	No
Over Underfloor Heating	Yes *

\* Subject to compatible subfloor and correct installation (see installation guidelines).

**Unfinished / Euro Oak (FSC certified) / Rustic Blocks**



<b>Grading Criteria</b>	
Maximum Knot Size	Sound up to 15mm max
Filled Defects	Allowed
Heart / Pith	Not allowed
Sapwood	Allowed
End Checks / Cracks	Up to 10mm max
Insect Damage	Not allowed
Filler	Allowed
Colour Variation	Natural variation allowed

N.B. Grading criteria is an approximation. Please allow for variation.

Origin	EU
EUTR	EUTR compliant
FSC	Yes
PEFC	-
SVLK	-
Moisture Content	8 - 10%
Janka Hardness Rating (Euro Oak)	6
Slip Testing	65 PTV
Fire Classification	Cfl-s1
Thermal Conductivity	0.11 W/m K
Emission of (release) formaldehyde	E-1
Breaking Strength (max. load) & span	NPD
Biological Durability	Class 1
Stain Resistance	Depends on finish applied
Acoustic Properties	N/A