

Unfinished / Euro Oak (FSC certified) / Prime Plank



Usage	Commercial & Residential Applications
Product Code	2WOP[THICKNESS]X180U BF
Thickness x Width	15 x 180mm, 20 x 180mm
Board Type	Engineered T&G
Pattern	1-strip plank (micro-bevel 2 sides)
Pack Length	1.8m, 2.1m, 2.4m (allowing 1 split board/pack)
Top Layer	4mm on 15mm thick & 6mm on 20mm thick
Timber Grade	Prime grade
Backing	Birch plywood
Surface Finish	Unfinished
Environmental Rating	A+
Maintenance	Dependant on the finish applied

Installation All floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Please check your installer is approved to BS8201.

Installation Methods	
Fully Bonded	Yes * recommended
Nailed	Yes
Floated Over Underlay	Yes
Over Underfloor Heating	Yes * **

* Subject to compatible subfloor and correct installation (see installation guidelines).

** Subfloor temperature must never be allowed to exceed 27 degrees centigrade.

Unfinished / Euro Oak (FSC certified) / Prime Plank



Grading Criteria	
Maximum Knot Size	Occasional sound knots <5mm
Filled Defects	Not allowed
Heart / Pith	Not allowed
Sapwood	Not allowed
End Checks / Cracks	Not allowed
Insect Damage	Not allowed
Filler	Not allowed
Colour Variation	Not allowed

N.B. Grading criteria is an approximation. Please allow for variation.

Origin	EU
EUTR	EUTR compliant
FSC	Yes
PEFC	-
SVLK	-
Moisture Content	8 - 10%
Janka Hardness Rating (Euro Oak)	1,360 lbf
Slip Testing	65 PTV
Fire Classification	15mm Cfl-s1, 20mm Dfl-s1
Thermal Conductivity	15mm 0.11 W/m K, 20mm 0.17 W/m K
Emission of (release) formaldehyde	E1
Breaking Strength (max. load)	20/6 - 5.4kN (60cms) 6.2kN (40cms), 15/4 - N/A
Cigarette Burns	Dependant on finish applied
Stain Resistance	Dependant on finish applied
Acoustic Properties	N/A